## Adgressor®

Rider Scrubbers







## Flexibility for every kind of clean.

The Advance Adgressor® rider-scrubber with EcoFlex™ System lets you clean green and still meet the highest expectations for clean floors. With the industry's most flexible floor-scrubber technology, you can develop a sustainable cleaning routine and quickly adjust to whatever the job demands. Be prepared to get more out of your budget, clean with less impact to the environment and maintain clean floors when you do.




Operators can quickly and easily select the right blend of pad pressure, water and detergent to tackle any cleaning challenge. Here are just a few of the flexible cleaning modes:

- Water Only Perfect for removing surface dirt and maintaining the clean look of floors. Water-only mode eliminates the impact of detergents on the environment and reduces cleaning costs.
- **Ultra-low Detergent** Well suited for routine cleaning where a small amount of green-certified detergent will do the trick. Water and detergent are dispensed separately at the scrub deck, eliminating solution waste.
- **Standard Detergent** The tough cleaning you expect. At standard detergent, pad pressure and flow rate, you'll have a combination powerful enough to pull stubborn dirt, grease, and oil from the surface.
- **Burst of Power** For deep, restorative cleaning or unexpected challenges. EcoFlex's burst of power temporarily increases your machine's pad pressure, detergent use and flow rate at the touch of a button.

The Adgressor is designed as a true industrial rider scrubber with reliability, productivity, and ease of use and maintenance built in. Combining large scrub decks and solution capacities with maneuverability and speed, the Adgressor delivers high productivity. A steel chassis and metal bumpers stand up to tough operating environments while thick rotomolded polyethylene tanks will not dent, crack, or corrode.

The Adgressor with EcoFlex System delivers the flexibility to clean your floors more efficiently. By using a system that cleans like you do, you'll reduce your cost to clean and create a more sustainable cleaning program.



- Comfortable full size operator compartment has excellent field of vision with Clear-View™ sight lines
- Large recovery tank opening provides easy, unobstructed cleaning
- One Touch™ control panel for all scrub functions. Includes all indicators/gauges
- Optional EcoFlex™ System offers green and clean flexibility
- Variable volume horn and backup alarm are standard
- High capacity and rugged polyethylene solution and recovery tanks are crack, dent and chemical resistant
- Steering column tilts for comfort and easy boarding




- Solution tank has EasyFlow drain hose, for clean and controlled dumping
- Mechanical safety brake with parking brake standard
- Metal bumpers for added 10 machine protection
- *UltraFlow*™ unique design increases air speed in squeegee for better pick up and dryer floors
- QuickChange<sup>™</sup> no tools interchangeable deck system
- Heavy-duty side skirts leave floors dry and safe

# Large Retail / Malls Stadiums and Arenas Municipalities **Government Buildings** Universities

**Distribution/Warehousing** 

Food and Beverage Light Manufacturing **Transportation Facilities** 




EcoFlex™ System models have One-Touch™ activation for an on-demand cleaning burst of power.



All systems start and stop with machine motion

### **MAXIMUM CLEANING PER HOUR** 66,880 ft<sup>2</sup>/hr 61,600 ft<sup>2</sup>/hr 56,320 ft²/hr Deck Deck 32"

The Adgressor® can grow with your company. The scrub deck interchangeability allows a larger, more productive scrub deck to be installed to address a growing company's increasing square footage.



The Adgressor® turns within a 63 inch (160 cm) aisle. This improves productivity by allowing the Adgressor to easily clean smaller aisles than the competition.

#### **Technical Specifications**

| Models                                      | Adgressor® 3220  | Adgressor® 3520                           | Adgressor® 3820            |
|---|--|---|----------------------------|
| Scrub Path                                  | 32 in (81 cm)  | 35 in (89 cm)                             | 38 in (97 cm)              |
| Max. Productivity at 4.0 mph                | 56,320 ft <sup>2</sup> /hr   | 61,600 ft²/hr                             | 66,880 ft²/hr              |
| Max. Productivity at 2.5 mph                | 35,200 ft <sup>2</sup> /hr   | 38,500 ft <sup>2</sup> /hr                | 41,800 ft <sup>2</sup> /hr |
| Solution Tank                               | 42 gal (157 L)   | 42 gal (157 L)                            | 42 gal (157 L)             |
| Recovery Tank                               | 42 gal (157 L)   | 42 gal (157 L)                            | 42 gal (157 L)             |
| Brush Drive                                 |  |   |                            |
| Disc  | 1.5 hp (1)   | 0.6 hp (3)                                | 0.6 hp (3)                 |
| Cylindrical                                 | Two 0.75 hp, 560 Watt motors on opposing ends, poly-V belt brush drive                                 |   |                            |
| Scrub Deck                                  |  |   |                            |
| Disc  | Manual-adjusting side skirts contain solution  |   |                            |
| Cylindrical                                 | Includes hopper for collecting small litter. Auto-adjusting side skirts contain solution               |   |                            |
| Brush Speed                                 | Disc 250 rpm, Cylindrical 900 rpm  |   |                            |
| Brush Pressure                              | Programmable 3 settings up to 250 lb (113 kg)  |   |                            |
| Drive System                                | 1.5 hp motor with gear transmission, band brake and dynamic braking.                                   |   |                            |
| Programmable speeds up to 4.5 mph (7.3 kph) |  |   | ph)                        |
| Gradeability                                | Transport - 20% / 11.5 deg., Working (scrubbing) - 8% / 4.6 deg  |   |                            |
| Min. Turn-around Aisle Width                | 63 inch (160 cm) with a 32 inch deck   |   |                            |
| Voltage                                     | 36 Volt for more power and longer run time   |   |                            |
| Power Source                                | 310 Ah or 420 Ah wet or 312 AGM maint-free battery options   |   |                            |
| Battery Charger                             | Option of shelf or onboard charger   |   |                            |
| Solution Control Cycles                     | Smart Solutions™ is standard providing better water and chemical utilization and fewer dump and refill |   |                            |
| Vacuum Motor                                | 0.75 hp 3-stage with optional dual vacuum  |   |                            |
| Sound Level                                 | 68 dB A at operator's position   |   |                            |
| Frame Dimensions                            | Length = 61 in (155 cm), Width = 32 in (82 cm), Height = 53 in (135 cm)                                |   |                            |
| Squeegee Width                              | 36.6 in (93 cm)  | 42.1 in (107 cm)                          | 45.1 in (115 cm)           |
| Weight                                      | Machine Only 657 lb (2   | 298 kg). With full tank and standard batt | eries 1,553 lb (705 kg)    |
| Optional EcoFlex™ System Specifications     |  |   |                            |
| Solution Flow Pump                          |  |   |                            |
| Dilution Ratios                             | 32:1, 50:1, 64:1, 100:1, 128:1, 150:1, 200:1, 256:1, 300:1   |   |                            |
| Refillable Cartridge Capacity               | 1.25 gal (4.75 L)  |   |                            |
| Battery Watering System                     |  | . J (/                                    |                            |

Specifications are subject to change without notice.





#### **Accessories and Options**

- Right side edging broom
- Headlight kit
- Safety strobe light kit
- Cool Tool™ Scrub & Vac™ kit
- Dual vac kit
- Onboard charger
- Battery water level indicator
- Dual arm rest kit
- Seat belt kit
- Rear scrubber compound tires
- Oil-resistant neoprene, squeegee and scrub deck blades
- Full range of brushes and pad holders for light to aggressive scrubbing

Visit http://www.advance-us.com or contact your Advance sales representative to learn more.





#### Green Meets Clean

- Flexible Performance Quickly and easily make adjustments for whatever the job demands.
- Fits Any Routine Develop an ideal routine for your staff, floors and budget.
- Cost Efficient Save time, use fewer machines, and reduce water and detergent consumption by cleaning more efficiently.
- Environmentally Responsible Reduces all of the environmental impacts in cleaning from the water and detergent to machine run-time and energy use.

#### Smart cleaning.

Our products are designed using innovative technologies that increase productivity and drive down the cost to clean.

Maintain peak performance with Nilfisk Parts.

#### Nilfisk, Inc.

9435 Winnetka Avenue North Brooklyn Park, MN 55445 www.advance-us.com Phone 800-850-5559 Fax 800-989-6566 240 Superior Boulevard Mississauga, Ontario, Canada L5T 2L2 www.nilfisk-advance.ca Phone 800-668-8400 Fax 800-263-5111

