



# SCB-1200-E Chassis W/SC-12 Scarifier Head Attachment

BW Manufacturing has produced the only mid-sized ride on surface preparation machine on the market. The SCB-1200 features a removable dust containment box with wheels for ease of dumping. The interchangeable heads give you the mobility and versatility to switch applications in minutes. Ergonomically designed one handed operation controls for raising and lowering heads, and easy to turn manual steering were designed with the contractor in mind. The SC-12 Scarifying Head attachment is a state of the art design that is self leveling, automatically adjusting itself to different contours of the floor or pavement. You will achieve an accurate removal of thin mill coatings to 1/4" overlays. Versatility is the key to the SCB-1200 with SC-12 Scarifier Head attachment. With quick change cages you can go from steel to carbide cutters as well as different cage widths in minutes. The SCB-1200 with SC-12 Scarifier Head Attachment will put you ahead of the competition with its faster production rates, and a vacuum collector system that eliminates dust and removes all material from the scarified surface.





## SCB-1200-E Specifications

<b><u>Interchangeable Head:</u></b>	Shotblast Scarifier Diamond Grinder Magnet/Broom
<b><u>Tires:</u></b>	Non-marking
<b><u>Length:</u></b>	81" (206cm)
<b><u>Width:</u></b>	35" (89cm)
<b><u>Height:</u></b>	54" (137cm)
<b><u>Weight:</u></b>	1200 lbs. (544kgs)
<b><u>Motor (230V/480V):</u></b>	25 hp
<b><u>3 Phase 230V 64 amps</u></b>	"
<b><u>3 Phase 480V 32 amps</u></b>	"
<b><u>Drive:</u></b>	Hydrostat
<b><u>Compressor:</u></b>	4.5 cfm.
<b><u>Vacuum:</u></b>	1480 cfm.
<b><u>Steering:</u></b>	Manual
<b><u>Collector Capacity:</u></b>	3.8 cubic ft.
<b><u>Aisle Width Min:</u></b>	54" (Blastable Width) (137cm)

### Scarifier Application

- Rubber Membrane Removal
- Concrete Milling
- Line Striping
- Bridge and Parking Decks



Cage W/ Carbide Cutters



Cage W/ Steel Cutters

## SC-12 Specifications

<b><u>Production Capacity†:</u></b>	500 to 1000 sfh (46 to 93 sqm)
<b><u>Cleaning Path:</u></b>	4" to 12" (10cm to 30cm)
<b><u>Width with attachment:</u></b>	40" (102cm)
<b><u>Weight:</u></b>	420 lbs. (191kgs)
<b><u>Aisle Width Min:</u></b>	54" (Scarifying Width) (137cm)

†Production rates achieved will be affected by variables specific to each job site. These figures are not guarantees of performance. For proper operation, the shot blasting unit must be used in conjunction with an appropriate dust collector.

Always wear appropriate eye, ear and respiratory protection for the application, as specified by OSHA regulations and your employer. Never operate or maintain equipment before reading and understanding the instructions for operation and maintenance. Obey all safety signs and instructions while operating or maintaining equipment.

**BW Manufacturing, Inc.**

3706 Mill Creek Drive NE  
Comstock Park, Michigan 49321 U.S.A.

Phone: 616-447-9076 • [BWMANUFACTURING.com](http://BWMANUFACTURING.com)

