

Burnishers

The Ultra Speed 20 battery burnisher delivers the smooth performance, consistent shine, and cleaner indoor air quality that is demanded by today's customers.

Operators of the Ultra Speed 20 will sense a whole new feel and experience when burnishing. A (stiffer) frame and nine vibration isolators have turned the operation of the Ultra Speed 20 into the smoothest burnishing experience in the market.

With an updated, double-pivot pad-driver design, the Ultra Speed 20 burnishing pad stays in alignment and allows the pad to follow the floor contours, leaving a more consistent gloss. Combining the pad-driver design with the self-regulating pad pressure, operators have an easy to use, battery walk-behind burnisher that saves labor time and dollars. Adding to the ease of operation is the self-lowering burnishing deck. When the palm switches on the handle are activated, the burnishing deck automatically lowers to the floor. When the palm switches are released, the deck automatically returns to a raised position. Simple controls also minimize training time of operators.

- 20 inch burnishing path powered by a 2.5 hp motor
- Self-regulating pad pressure no adjustment required
- Non-traction or power traction drive
- Easy tip back features makes it easy to change out pads
- On-board battery charger
- Class leading passive dust control
- Wet cell or AGM batteries

• Standard equipment

• Standard equipment



Picture shown may not represent model quoted

Model	ULTRASPEED 20T 200AH	ULTRASPEED 20 200AH	ULTRASPEED 20T 234AH AGM
Ref. no.	56383522	56383523	56383524

PRODUCT FEATURES

Vibration dampener	•	•	•
Compact design	•	•	•
Disposal bag	•	•	•
Angle Activated Safety Switch	•	•	•
Onboard charger (standard)	•	•	•
Low battery protection	•	•	•
Two port dust bag	•	•	•
Tip Back Design	•	•	•
Palm Switches	•	•	•
Reverse button	•	•	•
Superior Line of Sight	•	•	•



Burnishers

Model	ULTRASPEED 20 234AH AGM
Ref. no.	56383525

PRODUCT FEATURES

Vibration dampener	•
Compact design	•
Disposal bag	•
Angle Activated Safety Switch	•
Onboard charger (standard)	•
Low battery protection	•
Two port dust bag	•
Tip Back Design	•
Palm Switches	•
Reverse button	•
Superior Line of Sight	•

Technical specifications	ULTRASPEED 20T 200AH	ULTRASPEED 20 200AH	ULTRASPEED 20T 234AH AGM
Traction motor type			
Sound level	68 dB A	68 dB A	68 dB A
Drive wheels (cm)	1.62 in x 8 in (4 cm x 20 cm)	1.62 in x 8 in (4 cm x 20 cm)	1.62 in x 8 in (4 cm x 20 cm)
Pad pressure lbs (kg)	Self Regulating up to 30 lb (13 kg)	Self Regulating up to 30 lb (13 kg)	Self Regulating up to 30 lb (13 kg)
Pad speed (RPM)	2,000 rpm (on the floor)	2,000 rpm (on the floor)	2,000 rpm (on the floor)
Approx. shipping weight lbs (kg)	597 lb (271 kg) / 642 lb (291 kg)	597 lb (271 kg) / 642 lb (291 kg)	597 lb (271 kg) / 642 lb (291 kg)
Onboard charger standard	36 V, 25 A DC, 85-265 V / 45-65 Hz AC	36 V, 25 A DC, 85-265 V / 45-65 Hz AC	36 V, 25 A DC, 85-265 V / 45-65 Hz AC
Batteries	200 Ah / 234 Ah AGM	200 Ah / 234 Ah AGM	200 Ah / 234 Ah AGM
Length	50 in (127 cm)	50 in (127 cm)	50 in (127 cm)
Width	23 in (58 cm)	23 in (58 cm)	23 in (58 cm)
Height	41.25 in (105 cm)	41.25 in (105 cm)	41.25 in (105 cm)
Weight without batteries	551 lb (250 kg) / 596 lb (270 kg)	551 lb (250 kg) / 596 lb (270 kg)	551 lb (250 kg) / 596 lb (270 kg)
Pad motor	2.5 hp (1.9 kW)	2.5 hp (1.9 kW)	2.5 hp (1.9 kW)
Polishing rate (max.)	24,000 sq ft/hr (7,315 sq m/hr)	24,000 sq ft/hr (7,315 sq m/hr)	24,000 sq ft/hr (7,315 sq m/hr)
Polishing rate (practical)	17,600 sq ft/hr (5,365 sq m/hr)	17,600 sq ft/hr (5,365 sq m/hr)	17,600 sq ft/hr (5,365 sq m/hr)
Drive (traction or non-traction)	Non-Traction	Non-Traction	Non-Traction
Speed (forward/reverse)			



Burnishers

Technical specifications	ULTRASPEED 20T 200AH	ULTRASPEED 20 200AH	ULTRASPEED 20T 234AH AGM
Pad diameter	20 in (50.8 cm) Burnishing Path	20 in (50.8 cm) Burnishing Path	20 in (50.8 cm) Burnishing Path
Low battery protection	yes	yes	yes
Power	36 V, (3) 12 V batt.	36 V, (3) 12 V batt.	36 V, (3) 12 V batt.
Technical specifications			ULTRASPEED 20 234AH AGM
Traction motor type			
Sound level			68 dB A
Drive wheels (cm)			1.62 in x 8 in (4 cm x 20 cm)
Pad pressure lbs (kg)			Self Regulating up to 30 lb (13 kg)
Pad speed (RPM)			2,000 rpm (on the floor)
Approx. shipping weight lbs (kg)			597 lb (271 kg) / 642 lb (291 kg)
Onboard charger standard			36 V, 25 A DC, 85-265 V / 45-65 Hz AC
Batteries			200 Ah / 234 Ah AGM
Length			50 in (127 cm)
Width			23 in (58 cm)
Height			41.25 in (105 cm)
Weight without batteries			551 lb (250 kg) / 596 lb (270 kg)
Pad motor			2.5 hp (1.9 kW)
Polishing rate (max.)			24,000 sq ft/hr (7,315 sq m/hr)
Polishing rate (practical)			17,600 sq ft/hr (5,365 sq m/hr)
Drive (traction or non-traction)			Non-Traction
Speed (forward/reverse)			
Pad diameter			20 in (50.8 cm) Burnishing Path
Low battery protection			yes
Power			36 V, (3) 12 V batt.

● Standard equipment, ○ Supplementary accessories, □ Mountable equipment

Burnishers

● Standard equipment, ○ Supplementary accessories, □ Mountable equipment