SPE 12ES
SHOT BLASTER

SPE 12ES
SHOT BLASTER

SPE 12DC
DUST COLLECTOR

TECHNICAL SPECS | SPE 12ES

Voltage	230V/400V/460V
Phase	3 Phase
Blast Motor Output	10hp (7.5kw)
Cycles	50/60Hz
Cleaning Width	12" (305mm)
L x W x H	46.5" x 18.9" x 47.2" (1180mm x 480mm x 1200mm)
Weight	704lbs (320kg)

TECHNICAL SPECS | SPE 12DC

Type	3 Phase
Part Number	SPE 12DC
Voltage	400/460V
Cycles	50/60Hz
L x W x H	68.1" x 31.5" x 63" (1730mm x 800mm x 1600mm)
Weight	770lbs (350kg)
CFMS	1020/1220

FEATURES

- Blast unit constructed of manganese steel
- Dust collector fitted with integral compressor and reverse air jet pulsation system to allow continuous working
- Blasting width can be reduced for line removal and weld inspection
- Self propelled variable speed drive allows complete operator control
- Grill fitted into lower separator hopper unit assembly to eliminate foreign objects being allowed into the blastwheel causing damage
- Capable of using up to S550 abrasive
- Fully machined blastwheel support bearing assembly (eliminates bearing problems and automatically self-aligns blastwheel components)
- Blastwheel can be rotated in both directions (Optional extra)
- Can be dismantled to pass through a 600mm (23.6") access hole in storage tanks

SPE 9G | SPE 9ES | SPE 12ES | SPE 16ES | SPE 20ES | SPE 20ES ELECTRIC DRIVE