



EPOCH Dual Speed Rotary Sander

Patent Pending Design

- 1 Heavy duty rectified motor to provide more low end torque.
- 2 Dual speed capability for use with various grits, wood types, and job site conditions.
- 3 Removable weight bracket to provide better access to tight spaces.
- 4 Adjustable 11.3 kg weight kit allows for adjustments in sanding aggressiveness.
- 5 Bright, flexible LED light (with replaceable bulb) for improved visibility.
- 6 Ergonomic handle.
- 7 Heavy duty 152 mm wheels for added stability.
- 8 Dust control ready.
- 9 Durable rigid, low profile skirt contains dust and allows close access to wall lines (not shown).



PRODUCT DESCRIPTION

The Epoch is a dual speed, multi-purpose machine designed to meet the many demands of wood floor sanding. Used on low speed, the machine can be used as a traditional buffer for intercoat abrasion, fine finishing and polishing, or stain application. Used on high speed with the HydraSand, the Epoch acts as a planetary sander, abrading and flattening floors. Removable weights allow for various levels of adjustment.

RECOMMENDED PRODUCTS



AVAC dust containment systems are the perfect mix of power and portability. At 26 (115 liters) and 12 gallon (53 liters) capacities, both models are easy to transport and are available with optional H.E.P.A. filters.



The HydraSand attachment mounts to any rotary sander and utilizes six 5" (127 mm) pads mounted to a thick steel plate.

TECHNICAL DATA

Electrical Motor	1.5 hp / 1.1kW Heavy duty rectified motor, 230V / 50 Hz
Pad Driver	Included
Wheels	51 mm x 152 mm
Pad Speed	175 and 300 rpm
Power Cord	12.2 m
Dust Skirt	Reinforced nylon, quick removal
Sanding Distance To Wall	95 mm
Light Spec	Flexible LED, 25,000 hours, 7,500 lumens
Weight	Machine only - 43.1 kg Machine w/ weights - 54.4 kg Machine w/ weights & HydraSand - 59.9 kg
Warranty	Parts and Labor - 1 Year

Specifications are subject to change without notice.

AVAILABLE MODELS

07221A - 2-speed 230V / 50 Hz with HydraSand

