

FUSION DG

MULTI-PURPOSE DEGREASER WITH D-MARK FOR OUTSTANDING RUBBER MARK REMOVAL

Fusion DG is recognized by the USPEDA Design for the environment,. It instantly removes oily soils, removes rubber marks easily, contains only readily biodegradable ingredients, and concetrated for maximum economy use.

SPECIFICATIONS

- Appearance: Clear, yellow liquid
- Odor: Mild, characteristic
- Density (lbs/gal): 8.72
- pH (conc.): 10.6
- Refractive index: 1.3629
- Foam Generation: Moderate
- Stability: Stable
- Freeze/thaw stability: OK 3 cycles
- Shelf life: 1 year minimum
- D.O.T. classification: Not regulated
- Biodegradable: Yes
- Section 313 chemicals: None
- Volatile organic compounds (VOC): None

DIRECTIONS

- Wear safety equipment recommended on MSDS. Read all directions and cautions prior to beginning work. Remove loose soil and garbage. Before cleaning floors, place Wet Floor signs near work area.
- Dilute Fusion DG with water as follows: General Cleaning: 1:32 to 1:128 Floor with Tire Marks: 1:15 Heavy Tire Marks and Soils: 1:4 and 1:8
- Apply to surface liberally while scrubbing. Allow to work. If soil is heavy, double scrub with an autoscrubber (First pass, squeegee up; second pass, squeegee down, vac on). Pick up as much solution as possible. If possible, allow floor to dry before traffic resumes on cleaned area.



Available is sizes: 2.5, 55 gallon containers and 55 gallon Connex-Safe© for dispensing systems.

PROFESSIONAL RECOMMENDATIONS

- Use this product regularly for best results
- Use "grit" type brushes on your autoscrubber to enhance cleaning on unfinished concrete and other industrial floors
- Overlap your cleaning passes to assure uniform cleaning and "double scrub" when heavy soil is present.
- When mop cleaning, change cleaning solution frequently to get peak performance. Do not let mop rest in cleaning solution between uses

EQUIPMENT LIST

- Wet floor signs
- Autoscrubber with grit type brushes
- Wet vacuum
- Looped-end cotton mop
- Mop bucket with wringer
- Push broom

