

# SAFETY DATA SHEET

## **SECTION 1- CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION**

**Product ID:** 2066  
**Product Name:** BURN-OUT  
**Revision Date:** MAY 2, 2023  
**Manufacturer's Name:** JORDAN POWER EQUIPMENT  
**Address:** 281 SOUTHWEST AVE., TALLMADGE, OH 44278  
**Emergency Phone:** 1-800-535-5053  
**Information Phone Number:** 330.630.9444  
**Product/Recommended Uses:** Mark Remover, Pre-Spray and General Degreaser  
**USDA Rating:** C1

## **SECTION 2- HAZARDS IDENTIFICATION**

### **Classification:**

Acute Toxicity Oral - Category 4  
Skin Irritation - Category 2  
Skin Sensitizer - Category 1  
Eye Irritation - Category 2

### **Pictograms:**



### **Signal Word:**

Warning

### **Hazardous Statements – Health:**

H302 – Harmful if swallowed.  
H315 – Causes skin irritation.  
H317 – May cause an allergic skin irritation.  
H319 – Causes serious eye irritation.

### **Precautionary Statements – General:**

P101 – If medical advice is needed, have product container or label at hand.  
P102 – Keep out of reach of children.  
P103 – Read label before use.

### **Precautionary Statements – Prevention**

P264 – Wash hands thoroughly after handling.  
P280 – Wear protective gloves, protective clothing, eye protection and face protection.  
P272 – Contaminated work clothing should not be allowed out of the workplace.  
P270 – Do not eat, drink or smoke when using this product.  
P261 – Avoid breathing mists or vapors.

### **Precautionary Statements – Response**

P302 + P352 – IF ON SKIN: Wash with plenty of soap and water.  
P362 + P364 – Take off contaminated clothing and wash before reuse.  
P333 + P313 – If skin irritation or a rash occurs: Get medical attention.  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 – If irritation persists: Get medical attention.  
P301 + P312 – IF SWALLOWED: Call a Poison Center or doctor if you feel unwell.

### Precautionary Statements – Storage

No precautionary statement available.

### Precautionary Statements – Disposal

P501 – Dispose of contents and container in accordance with local, regional, national and international regulations.

## **SECTION 3 – COMPOSITION, INFORMATION ON INGREDIENTS**

CAS	Chemical Name	% By Weight
0000111-76-2	ETHYLENE GLYCOL MONOBUTYL ETHER	10 – 15
0005989-27-5	D-LIMONENE	0 - 5
0061790-12-3	TALL OIL	0 - 5
0000141-43-5	ETHANOLAMINE	0 - 2
0000064-02-8	EDTA TETRASODIUM SALT	0 - 1

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

## **SECTION 4 – FIRST-AID MEASURES**

### **Inhalation:**

Remove source of exposure or move person to fresh air and keep comfortable for breathing.  
If exposed/feel unwell/concerned: Get medical attention.

### **Eye Contact:**

If irritation occurs, cautiously rinse eyes with lukewarm, gently flowing water for 5 minutes, while holding the eyelids open. If eye irritation persists: Get medical advice/attention.

### **Skin Contact:**

Rinse/wash with lukewarm, gently flowing water and mild soap for at least 15 minutes or until product is removed. If skin irritation occurs or you feel unwell: Get medical advice/attention.

### **Ingestion:**

Rinse mouth. Give two glasses of water. If you feel unwell or if concerned: Get medical advice/attention. Do NOT induce vomiting unless under the advice/direction of doctor/POISON CENTER. Note: Never give anything by mouth to an unconscious or convulsing person. Keep person warm and quiet.

## **SECTION 5 – FIRE-FIGHTING MEASURES**

### **Suitable Extinguishing Media**

Will not burn. Use extinguishing media suitable for surrounding fire.

### **Unsuitable Extinguishing Media**

None known.

### **Fire-Fighting Procedures**

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel.

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

### **Special Protective Actions**

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

## **SECTION 6 – ACCIDENTAL RELEASE MEASURES**

### **Emergency Procedure**

Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area).

Do not touch or walk-through spilled material. Isolate hazard area and keep unnecessary people away. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

Pick up with mop or wet vac. Rinse spill area with large amounts of water in accordance with all federal, state and local laws.

#### **Recommended Equipment**

Safety glasses, gloves.

#### **Personal Precautions**

Avoid contact with skin, eye or clothing. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

#### **Environmental Precautions**

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

#### **Methods and Materials for Containment and Cleaning up**

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

### **SECTION 7 – HANDLING AND STORAGE**

#### **General**

Wash hands after use.

Do not get in eyes, on skin or on clothing.

Do not breathe vapors or mists.

Use good personal hygiene practices.

Eating, drinking and smoking in work areas is prohibited.

Remove contaminated clothing and protective equipment before entering eating areas.

#### **Ventilation Requirements**

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.

#### **Storage Room Requirements**

Keep container(s) tightly closed and properly labeled. Store in cool, dry, well-ventilated areas away from heat, direct sunlight and incompatibilities. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use.

Containers that have been opened must be carefully resealed to prevent leakage.

Store at temperatures between 40°F and 100°F.

FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY. FOR USE BY TRAINED PERSONNEL ONLY. KEEP FROM FREEZING.

### **SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### **Eye Protection**

Wear eye protection with side shields or goggles. Wear indirect-vent, impact, and splash resistant goggles when working with liquids. If additional protection is needed for entire face, use in combination with a face shield.

#### **Skin Protection**

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization. The type of protective equipment must be selected according to the concentration and amount of the substance at the specific workplace. Launder soiled clothes.

### Respiratory Protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or exceeds OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed.

### Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Chemical	OSHA TWA (mg/m3)	OSHA TWA (ppm)	OSHA STEL (mg/m3)	OSHA STEL (ppm)	OSHA Carcinogen	OSHA Skin designation	OSHA Tables (Z1.Z2.Z3)	ACGIH TWA (mg/m3)
ETHANOLAMINE	6	3					1	7.5
ETHYLENE	50	240				1	1	97
GLYCOL MONOBUTYL ETHER								

Chemical	ACGIH TWA (ppm)	ACGIH STEL (mg/m3)	ACGIH STEL (ppm)	ACGIH Carcinogen	ACGIH TLV Basis	ACGIH Notations	NIOSH TWA (mg/m3)	NIOSH TWA (ppm)
ETHANOLAMINE	3	15	6				8	3
ETHYLENE	20						24	5
GLYCOL MONOBUTYL ETHER								

Chemical	NIOSH STEL (mg/m3)	NIOSH STEL (ppm)	NIOSH Carcinogen
ETHANOLAMINE	15	6	
ETHYLENE			
GLYCOL MONOBUTYL ETHER			

"C" - Ceiling limit, (I) - Inhalable fraction, A4 - Not Classifiable as a Human Carcinogen, irr = irritation, URT = Upper Respiratory Tract

## **SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES**

Density	8.04 lb./gal
Density VOC	1.33 lb./gal.
% VOC	16.4%
Appearance	Clear Liquid
Odor Threshold	N.A.
Odor Description	Citrus Scent
pH	9
Water Solubility	Complete
Flammability	Will NOT Burn
Flash Point	N.A.
Viscosity	N.A.
Lower Explosion Level	N.A.
Upper Explosion Level	N.A.
Vapor Pressure	N.A.
Vapor Density	N.A.

Melting Point	N.A.
Freezing Point	N.A.
Low Boiling Point	N.A.
High Boiling Point	N.A.
Decomposition Point	N.A.
Auto Ignition Temperature	N.A.
Evaporation Rate	N.A.
VOC Composite Partial Pressure	N.A.

## **SECTION 10 – STABILITY AND REACTIVITY**

### **Stability**

The product is stable under normal storage conditions.

### **Conditions to Avoid**

Keep from freezing.

### **Incompatible Materials**

None known.

### **Hazardous Reactions/Polymerization**

Will not occur.

### **Hazardous Decomposition Products**

None known.

## **SECTION 11 – TOXICOLOGICAL INFORMATION**

### **Skin Corrosion/Irritation**

Causes skin irritation.

### **Serious Eye Damage/Irritation**

Causes serious eye irritation.

### **Carcinogenicity**

No data available

### **Germ Cell Mutagenicity**

No data available

### **Reproductive Toxicity**

No data available

### **Respiratory/Skin Sensitization**

May cause an allergic skin reaction.

### **Specific Target Organ Toxicity - Single Exposure**

No data available

### **Specific Target Organ Toxicity - Repeated Exposure**

No data available

### **Aspiration Hazard**

No data available

### **Acute Toxicity**

Harmful if swallowed.

### **0000111-76-2 ETHYLENE GLYCOL MONOBUTYL ETHER**

LC50 (female rat): 450 ppm (4-hour exposure) (2)

LC50 (male rat): 486 ppm (4-hour exposure) (2)

LD50 (oral, male weanling rat): 3000 mg/kg (1)  
LD50 (oral, 6-week old male rat): 2400 mg/kg (1)  
LD50 (oral, yearling male rat): 560 mg/kg (1)  
LD50 (oral, female rat): 530 mg/kg; 2500 mg/kg (1)  
LD50 (oral, male mouse): 1230 mg/kg (1)  
LD50 (oral, rabbit): 320 mg/kg (1)  
LD50 (dermal, male rabbit): 406 mg/kg (cited as 0.45 mL/kg) (1)

#### **0000141-43-5 ETHANOLAMINE**

LD50 (oral, rat): 1720 mg/kg (10); 2100 mg/kg (3); 2740 mg/kg (3,8)  
LD50 (oral, mouse): 700 mg/kg (10)  
LD50 (oral, guinea pig): 620 mg/kg (10)  
LD50 (oral, rabbit): 1000 mg/kg (10)  
LD50 (dermal, rabbit): 1018 mg/kg (cited as 1 mL/kg) (10)

#### **Potential Health Effects - Miscellaneous**

0000111-76-2 ETHYLENE GLYCOL MONOBUTYL ETHER

Can be absorbed through the skin in harmful amounts. May cause injury to the kidneys, liver, blood and/or bone marrow. Repeated overexposure may result in damage to the blood. Eye contact may cause corneal injury. Has been toxic to the fetus in laboratory animals at doses that are toxic to the mother.

### **SECTION 12 – ECOLOGICAL INFORMATION**

#### **Toxicity**

No data available.

#### **Persistence and Degradability**

No data available.

#### **Bio-Accumulative Potential**

No data available.

#### **Mobility in Soil**

No data available.

#### **Other Adverse Effects**

No data available

### **SECTION 13 – DISPOSAL CONSIDERATIONS**

#### **Waste Disposal**

Under RCRA, it is the responsibility of the user of the product, to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state, and local laws.

Empty containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

### **SECTION 14 – TRANSPORT INFORMATION**

#### **US DOT Information**

Not regulated.

#### **IMDG Information**

Not regulated.

#### **IATA Information**

Not regulated.

## **SECTION 15 – REGULATORY INFORMATION**

CAS	CHEMICAL NAME	% BY WEIGHT	REGULATION LIST
0000111-76-2	ETHYLENE GLYCOL MONOBUTYL ETHER	10 – 15	SARA313, CERCLA, SARA312, VOC, TSCA, ACGIH, OSHA
0005989-27-5	D-LIMONENE	0 – 5	SARA312, VOC, TSCA
0061790-12-3	TALL OIL	0 – 5	SARA312, TSCA
0000141-43-5	ETHANOLAMINE	0 – 5	SARA312, VOC, TSCA, ACGIH, OSHA
0000064-02-8	EDTA TETRASODIUM SALT	0 – 5	SARA312, TSCA

## **SECTION 16 – OTHER INFORMATION**

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG- Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center(US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

### **HMIS HAZARD CODE**

<b>HEALTH</b>	<b>1</b>
<b>FLAMMABILITY</b>	<b>0</b>
<b>REACTIVITY</b>	<b>0</b>

### **SAFETY GLASSES AND GLOVES**

Caution: HMIS ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks and 4 representing significant hazards or risks.

### **DISCLAIMER**

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.